Addited 914

Handheld Pneumatic Pressure Test Pump

- Generate 95% vacuum to 375 psi (25 bar) pressure
- Portable, only 3.3 lb
- Great stability and high resolution
- Minimal maintenance
- Hand-tight quick connectors





OVERVIEW

The 914 Pneumatic Pressure Test Pump is a hand operated pressure pump designed to generate pressure from 95% vacuum to 375 psi (25 bar). A high-quality screw press is designed for fine pressure adjustment, with an adjustment resolution up to10 Pa (0.1 mbar). A specially designed shut-off valve makes the pressure as stable as possible during calibration. A built-in gas-liquid isolator protects the pump from moisture and dirt to reduce the need for maintenance. Two hand-tight guick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The 914 is an ideal comparison test pump for pressure instruments calibration.

FEATURES

- Portable:
 - Only 3.3 lb (1.5 kg)
- Adjustment Resolution
 - 10 Pa (0.1 mbar)

High-quality screw press for fine pressure adjustment

Great Stability

A specially designed shut-off valve makes the pressure as stable as possible during calibration

- Durable and Minimal Maintenance Built-in gas-liquid isolator protects the pump from moisture and dirt
- Easy-to-use
- Hand-tight Quick Connectors

Allows easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches

SPECIFICATIONS

- Media: Air.
- Generated Pressure Range: 95% vacuum to 375 psi (25 bar) positive pressure
- Adjustment Resolution: 10 Pa (0.1 mbar).
- Material: Ram/adapters: SS Body: SS/aluminum Seals: Buna-N
- Connection

Hand-tight connectors for both test gauge and

reference gauge.

Test Gauge Connection: 1/4NPT female, 1/4BSP

female, or M20X1.5 female

Reference Gauge Connection: 1/4NPT female,

1/4BSP female, or M20X1.5 female

Dimensions

Height: 5.12" (130 mm)


Base: 9.45" (240 mm) x 4.72" (120 mm)

Weight: 3.3 lb (1.5 kg).

Warranty: 1 year

ORDERING INFORMATION

Model Number



Accessories included

O-ring: 20 pcs Manual: 1 pc

Optional Accessories

Model number	Description
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs). More information shown on page 53.
ADT103	Adapters and fittings, 1/4NPT (1/4BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs). More information shown on page 54.
ADT100-HTK	Hose test kit, 5 feet flexible hose, 15,000 psi, 1/4NPT male to 1/4NPT (1/8NPT, 1/2NPT, 1/4BSP, or M20X1.5) female hand-tight quick connector. More information shown on page 55.
9901-914	Carrying Case for one 914 pump and two 681 gauges or 672 calibrators
ADT914-MK	Maintenance kit for Additel 914 pump

Phone: 801-756-5570 Fax: 714-998-6999 Email: sales@additel.com